

Nanodispersed Plurimetallic Electrocatalysts for Direct Alcohol Fuel Cells.

**J.-M. Léger, C. Coutanceau, L. Dubau,
S. Rousseau and C. Lamy**

*Laboratory of Electrocatalysis, UMR 6503, CNRS-
University of Poitiers, 40 Avenue du Recteur Pineau,
86022 Poitiers Cedex, France*

Fuel cells are now widely recognized as very attractive devices to obtain directly electric energy from a chemical product. However, the final choice of the fuel is still difficult and it appears now that it depends greatly on the field of application. If hydrogen or hydrogen-rich gas obtained by reforming is clearly the best choice for stationary applications, the problem related to its storage shows leads to the necessity to propose alternative fuels to use directly in fuel cells. Since a long time now, the direct use organic fuels have been considered despite their rather low activity in comparison to hydrogen. Methanol is widely proposed as the best choice for mobile applications such a electric vehicles^(1,2). This is due mainly to its availability and to the easiness of its storage as a liquid. Numerous studies have shown that it is possible to improve its electroreactivity by using platinum-based electrocatalysts.

However, and more recently, the question of the toxicity of methanol becomes more crucial. It is clear that methanol is considered since a long time as a toxic product (mainly neurotoxic), in addition to possible environmental problems in relation to its large miscibility to water. Even if technical solutions can be envisaged to avoid or limit in a large extent leakage of methanol, for example during refueling, such kinds of problems in relation with environment need to be taken seriously into consideration for large scale applications such as electric vehicles.

From this observation, different strategies can be proposed. The use of other oxygenated organic fuels presenting a negligible or very low chemical toxicity, or the use of a specific fuel for a specific application. Ethanol appears to be an interesting alternative fuel for a wide utilization, even if its price appears actually too high. Its low toxicity added with its availability (from biomass) is an important positive point for its use as an alternative to methanol even if its reactivity is slightly lower. But from more specific uses, methanol remains a very attractive fuel, even if it is necessary to be cautious. As examples, for uses in mobile electronic devices (laptop, cellular phones...), methanol can be used if technical solutions involving tight and/or disposable reservoirs.

As pointed above, the use of alcohols as fuels needs to have efficient electrocatalysts for its oxidation. In addition, to overcome the problem of the cross-over of the fuel, due to the properties of the protonic membrane, the finding of cathodic electrocatalysts non sensitive to organic fuel is necessary.

Preparation of such catalysts is then of great importance. For the oxidation of alcohols, platinum-based

catalysts are necessary, typically Pt-Ru for methanol, but with a specific superficial composition. The preparation of nanoparticles of bimetallic system is necessary, with a narrow dispersion in size and with a desired composition.

A process proposed several years ago⁽³⁾ seems well-adapted to prepare chemically plurimetallic electrocatalysts. The method consists in the synthesis of colloidal precursors which prevent the formation of large metallic particles. Such a technique can be used for the preparation of unsupported as well as carbon-supported electrocatalysts suitable for fuel cell electrodes. Moreover, this technique can be developed with a wide range of metals.

As an example, it was possible to vary the composition of a platinum-ruthenium system in order to determine the optimum composition for the methanol electrooxidation. In fact, if a composition of 50-50 at% is widely considered as the optimum, and is commercially available for fuel cell electrodes, systematic experiments confirmed that, even for the case of nanoparticles (typically 1.5 to 2 nm diameter), the optimum composition is in the range 20 to 30 at% of ruthenium.

In the case of the electrooxidation of ethanol, Pt-Ru particles give interesting results (better than pure platinum nanoparticles), but the bimetallic system platinum-tin appears as the most active one. However, the optimum composition is still an open question and problems related to the stability of such bimetallic compounds still exist.

This route of preparation of nanophase materials from colloidal precursor can be also used for the synthesis of platinum-based electrodes for the oxygen (or air) reduction. These cathodic electrocatalysts should be insensitive to the presence of organic fuels coming from the anodic compartment by the cross-over process though the membrane. Modification of platinum by chromium or cobalt give encouraging results and this technique of preparation allows the formation of nanoparticles with the second metal at an oxidation state compatible with the electrocatalytical reduction of oxygen.

Acknowledgements

Part of this work was done under the framework of contracts with the french technologic research network "PACo" devoted to fuel cells.

References

- [1] C. Lamy, J.-M. Léger and S. Srinivasan, in *Modern Aspects of Electrochemistry*, J.O'M. Bockris, B.E. Conway and R.E. White (Eds.) Kluwer Academic/Plenum Publishers (New-York), Vol 34, (2001) 53.
- [2] C. Lamy and J.-M. Léger, in *Interfacial Electrochemistry*, A. Wieckowski (Ed.) Marcel Dekker, New-York, chap 48, (1999) 885.
- [3] H. Bönemann, W. Brijoux, R. Brinkmann, E. Dinjus, I. Jousen and B. Korall, *Angew. Chem. Int. Ed. Engl.*, 30 (1991) 1312.