

## **Preparation of Thin Layer Electrodes by Spray Method**

Jiri Vondrak,<sup>1</sup> Marie Sedlarikova,<sup>2</sup> Jiri Michalek<sup>3</sup> and Martin Pradny<sup>3</sup>

<sup>1</sup>Institute of Inorganic Chemistry, Academy of Sciences of Czech Republic  
Rez near Prague, 250 68  
Czech Republic

<sup>2</sup>Institute of Electrotechnology, Faculty of Electrical Engineering and Communication, VUT Brno  
Udolni 53  
Brno  
Brno, — 602 00  
Czech Republic

<sup>3</sup>Institute of Macromolecular Chemistry, Academy of Sciences of Czech Republic  
Heyrovskeho 2  
Praha 6  
Praha 6, — 160 00  
Czech Republic

Electrodes for electrochromic devices based on metallic oxides (tungsten, vanadium, titanium and their composites) were prepared by the spray method onto tin – oxide based layers prepared by the same method. The composition of the conductive layer played an important role on the performance of the electrodes. Electrical conductance, optical properties and electrochromic activity were measured in liquid PC electrolytes as well as in gel polymer ones.

Acknowledgment: This work was supported by Grant Agency of Academy of Sciences of Czech Republic (grant No. 403/0002), by Grant Agency of Czech Republic (grant No. 104/02/731) and by Ministry of Education of Czech Republic, MSMT (grant No. MSMT LN00A065).